



Dimension:unit(mm)



Model No.	Configuration	Voltage	Capacity	Nominal Rate	Charger Voltage Limit	Charger C urrent Limit	Approx Weight
EJBO24V-02A	Panasonic CGR18650CG -7S4P	24V	9.0Ah	216Wh	29.4V	3A	1.65-2.75Kg
EJBO24V-02B	Panasonic NCR18650-7S4P	24V	11.6Ah	278 Wh	29.4V	3A	1.65-2.75Kg
EJBO24V-02C	Samsung ICR18650-22F-7S4P	24V	8.8Ah	211 Wh	29.4V	3A	1.65-2.75Kg
EJBO24V-02D	Samsung ICR18650-26F -7S4P	24V	10.4Ah	249 Wh	29.4V	3A	1.65-2.75Kg
EJBO24V-02E	Panasonic CGR18650CH -7S4P	24V	8.8Ah	211 Wh	29.4V	5A	1.65-2.75Kg
EJBO24V-02F	Samsung ICR18650-22P -7S4P	24V	8.4Ah	201 Wh	29.4V	5A	1.65-2.75Kg

● Cycle Life

Standard charge mode, keep for 30min;Standard discharge mode:>500cycle,70%

● Standard Charge Model

Charge to 42V with constant current ,then charge with constant voltage till current less than 300mA.

Use special charger:CC+CV,2A,42V/300mA

● Options

Standard BMS: overcharge protection, overdischarge protection ,overcurrent protection balance&high temperature protection

Smart BMS,Standard BMS functions,scale,communication,sleep,encode,tailights blinking,5V USB output

● Certificate

FCC,CE,MSDS



Manufacturer reserves the right to alter or amend the approval sheet without the prior notice