

Cylindrical LiSOCL2 Battery Cells (Bobbin type)

International Model Size	Model	Nominal Voltage (V)	Nominal Capacity (mAh)	Max Dimensions (mm)	Max Continuous Operating Current (mA)	Approx Weight (g)
AAA	ER10450	3.6	600(1mA)	φ10.4X45.3	25	8
	ER11120	3.6	100(0.2mA)	φ11.5X12.0	2	2
	ER13150	3.6	450(0.5mA)	φ13.5X15.0	10	6
L31	ER13460	3.6	1500(1mA)	φ13.5X46.0	60	14
1/2AA	ER14250	3.6	1200(0.5mA)	φ14.5X25.0	20	10
2/3AA	ER14335	3.6	1650(1.3mA)	φ14.5X33.5	75	13
AA	ER14505	3.6	2400(2mA)	φ14.5X50.5	100	22
2/3A	ER17335	3.6	2100(2mA)	φ17.0X33.5	100	21
A	ER17505	3.6	3400(4mA)	φ17.0X50.5	120	25
A	ER18505	3.6	4000(2mA)	φ18.8X50.5	120	30
C	ER26500	3.6	8500(3mA)	φ26.2X50.0	130	53
D	ER34615	3.6	19000(2mA)	φ34.0X61.5	200	108
CC	ER261020	3.6	15000(mA)	φ26.2X102.0	200	100
DD	ER341245	3.6	33000(4.5mA)	φ34.2X124.5	230	200

High Power LiSOCL2 Battery Cells(Spiral Type)

International Model Size	Model	Nominal Voltage (V)	Nominal Capacity (mAh)	Max Dimensions (mm)	Max Continuous Operating Current (mA)	Approx Weight (g)
1/2AA	ER14250M	3.6	750(4mA)	φ14.5X25.2	10	120
2/3AA	ER14335M	3.6	1200(4mA)	φ14.5X33.5	13	300
AA	ER14505M	3.6	1800(10mA)	φ14.5X50.5	22	500
2/3A	ER17335M	3.6	1700(5mA)	φ17.0X33.5	21	500
	ER17450M	3.6	2500(5mA)	φ17.0X45.0	23	800
	ER17505M	3.6	2700(5mA)	φ17.0X50.5	25	1000
	ER18505M	3.6	3500(5mA)	φ18.8X50.5	32	1000
	ER20505M	3.6	3800(5mA)	φ20.0X50.5		1000
	ER20505M	3.6	3600(10mA)	φ26.2X50.5	35	800
C	ER26500M	3.6	6500(10mA)	φ26.2X50.0	53	1000
D	ER34615M	3.6	14000(10mA)	φ34.0X61.5	108	2000

Wafer LiSOCL2 Battery Cells

International Model Size	Model	Nominal Voltage (V)	Nominal Capacity (mAh)	Max Dimensions (mm)	Max Continuous Operating Current (mA)	Approx Weight (g)
1/6D	ER32100	3.6	1700(1mA)	φ32.9X10.0	20	25
1/10D	ER3265	3.6	1000(1mA)	φ32.9X6.5	20	17

Prismatic LiSOCL2 Battery Cells

International Model Size	Model	Nominal Voltage (V)	Nominal Capacity (mAh)	Max Dimensions (mm)	Max Continuous Operating Current (mA)	Approx Weight (g)
LTC-3PN	EF651615	3.6	400(0.5mA)	16.8X15.8X6.8	5	5

LTC-7PN	EF651625	3.6	750(1mA)	16.8X25.8X6.8	10	8
LTC-16M	EF702338	3.6	16000(1mA)	23.3X38.3X7.2	20	19

High Temperature LiSOCL2 Battery Cells(Cylindrical Type)

Size	Model	Nominal Voltage (V)	Nominal Capacity (mAh)	Dimensions		Approx Weight (g)	Temperature
				Diameter (mm)	Height (mm)		
1/2AA	ER14250S	3.6	800	14.7	25.4	10	-40°C ~ +150°C
AA	ER14505S	3.6	1600	14.7	50.5	19	-40°C ~ +150°C
C	ER26500S	3.6	6000	26.9	50	52	-40°C ~ +150°C
D	ER34615S	3.6	13000	33.9	61.5	100	-40°C ~ +150°C

High Temperature LiSOCL2 Battery Cells(Coin Type)

Size	Model	Nominal Voltage (V)	Nominal Capacity (mAh)	Dimensions		Approx Weight (g)	Temperature
				Diameter (mm)	Height (mm)		
1/2AA	ER14250T	3.6	1000	14.7	25.4	10	-60°C ~ +125°C
	ER2450T	3.6	400	24.5	6.2	9	-60°C ~ +125°C
	ER1860	3.6	280	18.2	6.5	5.5	-60°C ~ +125°C

High Temperature LiSOCL2 Battery Cells(Prismatic Type)

Size	Model	Nominal Voltage (V)	Nominal Capacity (mAh)	Dimension			Approx Weight (g)	Temperature
				Length (mm)	Width (mm)	Thickness (mm)		
LTC-7PN	EF651625T	3.6	750	16.8	25.8	6.8	8	-60°C ~ +125°C
LTC-3PN	EF651615T	3.6	400	16.8	15.8	6.8	8	-60°C ~ +125°C